



### QUICK SPECS

Rated Operating Capacity	2100 lbs (953 kg)
Net Power	70.7 hp (52.7 kW) @ 2500 rpm
Operating Weight - approx.	9890 lbs (4486 kg)
Lift Height	128 in (3251 mm)

## The go-to machine that makes you the go-to guy.

Extra horsepower or more lift height often goes a long way to help save the day. You get both, along with traction for muddy, uneven surfaces, in the Yanmar T210 Compact Track Loader. Plus, when your job calls for more than just loading and lifting, the T210 can run just about any kind of attachment you can think of.

### INNOVATIVE FEATURES



#### 70.7-HP YANMAR TURBOCHARGED DIESEL ENGINE

With Yanmar's Interim Tier 4 turbocharged diesel engine you'll never have trouble finding the power to dig up gnarly stumps or lift granite blocks. You won't have to worry that you have a diesel-guzzler on your hands, either. Even with up to 206 ft. lbs. of torque, these engines always run cleanly and efficiently.



#### AUTOMATIC TRACK TENSIONING

Instead of wasting time adjusting track tension all day, enjoy having it done constantly while you work with our industry-exclusive Automatic Track Tensioning System.



#### ANTI-STALL HYDROSTATIC PUMP

You can't afford to have an engine quit on you when the going gets tough. Yanmar's Anti-Stall technology automatically adjusts the hydrostatic pump, so even as drive load increases, maximum engine torque and drive power are constantly maintained.

## T210

COMPACT TRACK LOADER

POWERFUL YANMAR 70.7-HP TURBOCHARGED DIESEL ENGINE

AUTOMATIC TRACK TENSIONING SYSTEM

SELF-ADJUSTING HYDROSTATIC PUMP

5 X 5 DRIVE CONTROL SYSTEM STANDARD

STATE-OF-THE-ART CAB ERGONOMICS FOR COMFORT AND VISIBILITY

7.8-MPH GROUND SPEED

BEST-IN-CLASS TRACTIVE EFFORT AT 12,349 LBS.

BEST-IN-CLASS 37-IN. REACH

95.7-IN DUMP HEIGHT

CHOICE OF TWO QUICK COUPLER SYSTEMS

HIGH-FLOW HYDRAULICS

WELDED, DEDICATED TRACK SYSTEM FOR SMOOTHER RIDE

OPTIMIZED RADIAL-LIFT BOOM WITH BEST-IN-CLASS 128-IN LIFT HEIGHT



# T210

## COMPACT TRACK LOADER

# specifications

### ENGINE

Make/Model	Yanmar/4TNV98-XNMS Interim Tier 4
Type	4-Stroke Turbo
Displacement	203 cu.in. (3.319 L)
Cylinders	4
Net Horsepower @ 2500 rpm	70.7 hp (52.7 kW)
Peak Torque @ 1600 rpm	206 ft-lbs (279.3 Nm)
Oil Pump Capacity	11 qts (10.4 L)
Alternator Voltage/Amperage	12V/95A

### CAPACITY

Operating Capacity at 35% of Tipping Load	2100 lbs (953 kg)
Operating Capacity at 50% of Tipping Load	3000 lbs (1361 kg)
Tipping Load	6000 lbs (2722 kg)
Operating Weight	9890 lbs (4486 kg)

### VOLUME

Fuel Tank	24.4 gal (92 L)
Hydraulic Reservoir	13.8 gal (52.2 L)
Coolant Capacity	3.8 gal (14.4 L)

### FORCES

Bucket Breakout - Tilt Cylinder	5492 lbs (2491 kg)
Bucket Breakout - Lift Cylinder	5398 lbs (2449 kg)
Ground Speed - Single Speed	5.4 mph (8.7 km/hr)
Ground Speed - Two Speed	7.9 mph (12.7 km/hr)

### TRACK DRIVES

Drawbar Pull / Tractive Effort	12,359 lbs (5606 kN)
Track Type	Rubber
Track Rollers	4
Roller Type	Steel
Track Width	17.7" (450 mm)
Ground Pressure	4.7 psi (0.32 bar)

### DIMENSIONS

Overall Operating Height - Fully Raised	172" (4369 mm)
Height to Hinge Pin - Fully Raised	128" (3251 mm)
Reach - Fully Raised	37" (340 mm)
Dump Angle - Fully Raised	39°
Dump Height - Fully Raised	95.7" (2431 mm)
Maximum Rollback Angle - Fully Raised	102.5°
Overall Height at ROPS	83.1" (2111 mm)
Overall Length with Bucket - Standard Counterweight	152.3" (3868 mm)
Overall Length without Bucket - Standard Counterweight	114.5" (2908 mm)
Specified Height	67.7" (1720 mm)
Reach at Specified Height	31.8" (808 mm)
Dump Angle at Specified Height	75°
Maximum Rollback Angle at Ground	30°
Carry Position	7" (179 mm)
Maximum Rollback Angle at Carry Position	33°
Digging Position - Below Ground	-0.2" (5.1 mm)
Angle of Departure with Standard Counterweight	29.2°
Ground Clearance	13" (330 mm)
Track Gauge	51.7" (1313 mm)
Track Shoe Width	17.7" (450 mm)
Crawler Base	58.4" (1483 mm)
Overall Width - Less Bucket	69.5" (1765 mm)
Bucket Width	73.9" (1877 mm)
Clearance Radius - Front with Bucket	98.1" (2492 mm)
Clearance Radius - Rear with Standard Counterweight	64.6" (1641 mm)
Maximum Rollback at Specified Height	66.8°
Angle of Approach	90°
Grouser Height	1" (25 mm)

### HYDRAULICS

Auxiliary Hydraulic Flow - Rated Speed	21.8 gpm (82.5 L/min)
High-Flow Hydraulic Flow - Rated Speed	35.9 gpm (135.8 L/min)
Transmission Pump Type	Axial Piston
Motor Type	Axial Piston with Planetary Reduction