

VIMEK®

# 606 TT SE

Well proven, Swedish made machine that delivers driving pleasure and indispensable assistance in gentle forestry work.

LED lightning



Wide accessory program such as bucket attachment and Boogie tracks



Gentle on the ground and environment thanks to its low weight

3,000 kg loading capacity  
More than its own weight

Broad cabin with improved driver environment

Mechanical diesel engine without complicated electronics and with low fuel consumption

Articulated centre with hydraulic lock  
Stable in all modes so you don't have to hassle with support legs

Disconnectable wheel drive enables transportation on a dolly trailer

**VIMEK**

FASSI GROUP

# Equipment

- Pneumatic chair
- Diesel engine heater
- Callstarter diesel engine heater
- Crane damping system
- Sun blinds
- LED lightning
- Air conditioning
- Hydraulic radio controlled winch
- Radio with Bluetooth
- 220 volt engine heater
- Energy wood head
- Boogie tracks
- Wheel chains
- Bucket attachment
- Chainsaw holder
- Dolly trailer



All Vimek forwarders (in Sweden) are registered as heavy off-road vehicles, which means that they are allowed on public roads.

# VIMEK® 606 TT SE

## Technical specifications

<u>Engine</u> Kubota D 902-E, 18 kW/3600 rpm	<u>Width</u> 1.80 m
<u>Transmission</u> Variable mechanical	<u>Weight</u> From 2,900 kg
<u>Tyres</u> Front: 405/70-24 Rear: 400/60-15.5	<u>Loading area</u> Loading area 3.0 m with cargo space 1.4 m <sup>2</sup>
<u>Hydraulic</u> 43 L/min 175 bar	<u>Loading capacity</u> 3,000 kg
<u>Ground clearance</u> 40 cm	<u>Crane</u> Vimek – Mowi 2046 Range: 4.60 m
<u>Length</u> Standard: 6.20 m Long: 6.70 m	<b>Lifting capacity: 4.6 m 375 kg</b> <b>Gripping area: 0.16 m<sup>2</sup></b>

The machines displayed may be extra equipped.  
© 2022 Vimek AB. All rights reserved.  
Version 1, Mars 2022  
[www.vimek.com](http://www.vimek.com)

**VIMEK**

**FASSI GROUP**