

MULCHING POWER. Hardened Reliability. Leading Versatility.



Welcome the new MAX-Series[™] VT-80-1C Forestry Posi-Track[®] compact track loader. Despite its mid-sized frame, the machine packs a heavy punch to play with big forestry equipment while meeting forestry equipment safety standards – one of the industry's only compact track loaders to do so. High flow performance comes standard for optimal performance while running mulchers. Operators benefit from extra guarding, a polycarbonate door, rollover and falling object protection and an emergency roof escape hatch. And whether traversing a construction or landscaping jobsite or traveling through the woods, maximum traction and industry-leading ground clearance and departure angles mean less risk of getting hung up on obstacles or tricky ground conditions. Be a Force in Nature with the VT-80-1C Forestry.

// FORESTRY-GRADE SAFETY. POWERFUL PRODUCTVITY. PREMIUM VERSATILITY.



MAX-SERIES VT-80-1C FORESTRY COMPACT TRACK LOADER

OPERATING SPECIFICATIONS		
LOADER ARMS		Vertical
OPERATING WEIGHT		9,645 lbs (4,375 kg)
SHIPPING WEIGHT		8,911 lbs (4,042 kg)
GROUND PRESSURE AT OPERATING WEIGHT		4.2 psi (28.9 kPa)
RATED OPERATING CAPACITY (35% of tipping load)		2,800 lbs (1,270 kg)
OPERATING CAPACITY (50% of tipping load)		4,000 lbs (1,814 kg)
TIPPING LOAD		8,000 lbs (3,629 kg)
TRAVEL SPEED, MAXIMUM- 1 ST SPEED		6.1 mph (9.8 kph)
TRAVEL SPEED, MAXIMUM- 2 ND SPEED		9.1 mph (14.6 kph)
ENGINE		
ТҮРЕ	Diesel, 4-cylinder, intercooled, turbocharged	
MODEL	Yanmar 4TN86CHT	
GROSS POWER RATING AT 2600 RPM	71.5 hp (53.3 kW)	
TORQUE, PEAK	193.8 ft-lb (262.8 Nm)	
COOLING SYSTEM	Belt-driven fan and anti-freeze filled radiator cooling system	
INTAKE AIR CLEANER	Dual-Stage	
EMISSION CONTROLS	Meets all U.S. EPA Tier 4 final standards	
FUEL TANK CAPACITY	21.4 gal (81 l)	
UNDERCARRIAGE		
TRACK TYPE: General purpose track constructed of rubber compound with embedded co-polymer cords and all-purpose treads.		
TRACK WIDTH	17.7 in. (450 mm)	
LENGTH OF TRACK ON GROUND	64.5 in. (1,638 mm)	
GROUND CONTACT AREA	2,283 in. ² (1.47 m ²)	
DRIVE SYSTEM	Two hydrostatic dire single joystick	ect drive sprockets controlled by

Elevated with low-friction, replaceable sprocket rollers

Two independent torsion axles per undercarriage

Front & rear wheels: 14 in. (355.6 mm))

Middle wheels: 10 in. (254 mm)

12 high-density polyurethane and rubber wheels per track. Wheels include sealed bearings

AUXILIARY HYDRAULIC SYSTEM		
STANDARD PUMP CAPACITY	24.7 gpm (93.5 lpm)	
OPTIONAL HIGH FLOW	34.3 gpm (129.8 lpm)	
SYSTEM PRESSURE, MAX.	3,771 psi (26,000 kPa)	
CONTROLS	Intermittent via joystick button or continuous via console switch	
COUPLERS	1/2 in. Flat Face Couplers	
COOLING SYSTEM	High efficiency side-by-side radiator and oil cooler	
ELECTRICAL SYSTEM		
NOMINAL CHARGE	12 V	
BATTERY	800 CCA	
CHARGING SYSTEM	80 amp alternator	
OUTLETS	1-12 V port inside operator station	
WIRING	Pre-wired for all factory-available accessories	
OPERATOR STATION		
SEAT: Vinyl seat with built in operator presence switch, Operator Manual pouch, and 2 in. (51 mm) wide seat belt, adjustable position seat optional		
CONTROLS: Electronic joystick controls with ISO or H pattern settings, adjustable operator profiles and speeds		
ENGINE SPEED	Hand-operated dial and foot throttle	
coolant temperature, battery volta monitoring, fault logging. Deluxe i	ngine oil pressure, hydraulic oil high temperature, engine uge, hour meter, fuel level, trip meter, engine diagnostics, system ncludes: 7" color touch screen, integrated rear view camera, ofiles, job clock, maintenance schedules	
ROPS	ISO 8082-Forestry	
FOPS	ISO 8083-Forestry	
ILLUMINATION	 2 - Fixed forward-facing LED lights 2 - Adjustable rear-facing LED lights 2 - LED side lights (optional) 1 - Interior light 	
CONVENIENCE	12 V power port	
STANDARD FEATURES	Horn, backup alarm, cup holder, phone holder, behind seat storage, rear view mirror, lap bar, roof escape hatch, roof panel & rear cab windows. Premium Features: Adjustable joystick & arm rest positions, adjustable directional & air flow HVAC vents, radio with bluetooth & USB, frameless front door, attachment control kit, winer/washer, beacon switch/outlet	

& arm rest positions, adjustable directional & air flow HVAC vents, radio with bluetooth & USB, frameless front door, attachment control kit, wiper/washer, beacon switch/outlet, easy-off door





TRACK DRIVE SPROCKET

ROLLER WHEELS

UNDERCARRIAGE SUSPENSION

ROLLER WHEEL DIAMETER